

**BRADY B-1161 POLYETHYLENE CLING FILM**

TDS No. B-1161  
Effective Date: 10/31/2017

**Description:**

**GENERAL**

**Material Type:** Clear multi-layer polyethylene cling film (liner mounted)

**Print Technology:** Not printable

**APPLICATIONS**

Identification and protection of delicate surfaces

**REGULATORY**

Brady B-1161 is RoHS compliant to 2002/95/EC.

**SPECIAL FEATURES**

B-1161 is simple to apply and is cleanly removable from surfaces. This material has good clarity and conformability.

**Details:**

PHYSICAL PROPERTIES	AVERAGE RESULTS
Thickness	ASTM D1000 -Substrate 0.0040 inch (0.10 mm) -Liner 0.0035 inch (0.09 mm) -Total 0.0075 inch (0.19 mm)
Adhesion to: -glass surface	ASTM D1000 ( 20 minute dwell) 0.055 oz/in minimum (0.06 N/100 mm)

PERFORMANCE PROPERTIES	AVERAGE RESULTS
Chemical resistance -unprinted film	Excellent water resistance; can be wiped clean using water and soft household detergent. Immersion not recommended in most esters, ketones, gasoline, etc.
UV Light Resistance	No appreciable yellowing after normal exposure. Good fade resistance.
Shrinkage	1 minute after separation from paper backing at 21°C (70°F) Machine direction shrinkage: -2% Transverse direction shrinkage: +1%
Optical Transparency	Transparent; hardly visible fish-eyes, flow lines or processing marks
Dimensional stability	No measurable shrinkage on applied parts
Service Temperature	-20°C to 50°C (-5°F to 122°F)
Application Temperature	Minimum +15°C (59°F)
Expected Service Life	2 years indoors, 6 months outdoors

Shelf life is two years from the date of receipt for this product as long as this product is stored in its original packaging in an environment below 80° F (27° C) and 60% RH. It remains the responsibility of the user to assess the risk of using this product. We encourage customers to develop testing protocols that will qualify a product's fitness for use in their actual application.

**Trademarks:**

ASTM: American Society for Testing and Materials (U.S.A.)

**Note:** All values shown are averages and should not be used for specification purposes.

Test data and test results contained in this document are for general information only and shall not be relied upon by Brady customers for designs and specifications, or be relied on as meeting specified performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact Brady for further information.

Product compliance information is based upon information provided by suppliers of the raw materials used by Brady to manufacture this product or based on results of testing using recognized analytical methods performed by a third party, independent laboratory. As such, Brady makes no independent representations or warranties, express or implied, and assumes no liability in connection with the use of this information.

#### **WARRANTY**

Brady products are sold with the understanding that the buyers will test them in actual use and determine for themselves their adaptability to their intended uses. Brady warrants to the buyers that its products are free from defects in material and workmanship, but limits its obligation under this warranty to replacement of the product shown to Brady's satisfaction to have been defective at the time Brady sold it. This warranty does not extend to any persons obtaining the product from the buyers. This warranty is in lieu of any other warranty, express or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose, and of any other obligations or liability on Brady's part. Under no circumstances will Brady be liable for any loss, damage, expense, or consequential damages of any kind arising in connection with the use, or inability to use, Brady's products.

Copyright 2018 Brady Worldwide, Inc. | All Rights Reserved  
Material may not be reproduced or distributed in any form without written permission.