

## BRADY B-611 INDOOR WHITE FILM

TDS No. B-611

Effective Date: 11/07/2017

### **Description:**

Inkjet printable white film media

### **Details:**

### **Box ID:**

CPP or CPP54 FILM WH

### **Use:**

Pictorial images of high quality

### **Media Type:**

Coated and filled polypropylene film

### **Characteristics:**

Non-glare surface

Fast dry times

### **To be used with:**

ColorPix™ 3600 System

ColorPix™ Pro 36 System

ColorPix™ Pro 54 System

### **Typical Weight:**

53 lbs/3000 ft<sup>2</sup> (87g/m<sup>2</sup>)

### **Total Thickness:**

0.0054" (0.137 mm)

### **Material Length/Packaging Unit/Box:**

24" x 85' x 2 rolls (610 mm x 26 meters)

36" x 111' x 1 roll (915 mm x 34 meters)

54" x 230' x 1 roll (1370 mm x 70 meters)

### **Image Durability:**

12 months in outdoor use with outdoor ink and laminating film, sealed up both sides and at the edges. Life in use will be affected with finishing of printing surface and environmental conditions

### **Shelf Life:**

Shelf life is two years from the date of receipt for this product as long as this product is stored in its original packaging in an environment below 80° F (27° C) and 60% RH. It remains the responsibility of the user to assess the risk of using this product. We encourage customers to develop testing protocols that will qualify a product's fitness for use in their actual application.

### **Transportation Temperature:**

5°F to 122°F (-15°C to 50°C)

### **Recommended Printing Temperature:**

59°F to 86°F (15°C to 30°C)

### **Remarks:**

Water droplets will make spots on the surface of printout and reduce quality. If printout is stored in high temperature and humidity, the printout tends to become slightly red in color. Do not pile up the printouts one on another.

**Trademarks:**

ColorPix™ is a trademark of Brady Worldwide, Inc.

All U.S. Conventional Units are mathematically derived from the S.I. (metric) Units

**Note:** All values shown are averages and should not be used for specification purposes.

Test data and test results contained in this document are for general information only and shall not be relied upon by Brady customers for designs and specifications, or be relied on as meeting specified performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact Brady for further information.

Product compliance information is based upon information provided by suppliers of the raw materials used by Brady to manufacture this product or based on results of testing using recognized analytical methods performed by a third party, independent laboratory. As such, Brady makes no independent representations or warranties, express or implied, and assumes no liability in connection with the use of this information.

**WARRANTY**

Brady products are sold with the understanding that the buyers will test them in actual use and determine for themselves their adaptability to their intended uses. Brady warrants to the buyers that its products are free from defects in material and workmanship, but limits its obligation under this warranty to replacement of the product shown to Brady's satisfaction to have been defective at the time Brady sold it. This warranty does not extend to any persons obtaining the product from the buyers. This warranty is in lieu of any other warranty, express or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose, and of any other obligations or liability on Brady's part. Under no circumstances will Brady be liable for any loss, damage, expense, or consequential damages of any kind arising in connection with the use, or inability to use, Brady's products.

Copyright 2018 Brady Worldwide, Inc. | All Rights Reserved  
Material may not be reproduced or distributed in any form without written permission.