

## B230 Silicone Gel Copolyester Medical Tape

TDS No. B-230

Effective Date: 10/30/2017

### Description:

#### General

Face stock: 3 mil Elastic Copolyester Film  
Adhesive: Medical Grade Silicone Gel  
PSA Mils / Coat weight: 6 mils/ 100 lbs per rm  
Liner: 2 mil PET

### Details:

#### Typical Adhesive Properties

Peel Adhesion: 30-50 Grams/in  
Test Method:  
ASTM-D3330/ASTM-D1000  
180 Initial at 20  
minute dwell @ RT

Polyken Probe Tack: 75-95 grams/in<sup>2</sup>  
Test Method:ASTM-D2979

### APPLICATIONS

- Sensitive skin and neonatal applications
- Wound healing
- Skin therapy
- Medical device attachment
- Scar management

### PRODUCT BENEFITS

- Gentle adhesion
- Removes easily without causing skin trauma
- Non-irritating and skin friendly for sensitive areas of the body
- Soft and repositionable
- Conformable backing

### PRODUCT SAFETY

"ISO 109931 2003 Biological Evaluation of Medical Devices Part 1: Evaluation and Testing" indicate that all tested materials pass all biocompatibility tests conducted.

1. Cytotoxicity
2. Skin irritation
3. Sensitization potential in Guinea pigs
4. Hemolysis direct contact and extract
5. Pyrogenicity material mediated

### Shelf Life:

Shelf life is two years from the date of receipt for this product as long as this product is stored in its original packaging in an environment below 80° F (27° C) and 60% RH. It remains the responsibility of the user to assess the risk of using this product. We encourage customers to develop testing protocols that will qualify a product's fitness for use in their actual application.

**Trademarks:**

**Note:** All values shown are averages and should not be used for specification purposes.

Test data and test results contained in this document are for general information only and shall not be relied upon by Brady customers for designs and specifications, or be relied on as meeting specified performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact Brady for further information.

Product compliance information is based upon information provided by suppliers of the raw materials used by Brady to manufacture this product or based on results of testing using recognized analytical methods performed by a third party, independent laboratory. As such, Brady makes no independent representations or warranties, express or implied, and assumes no liability in connection with the use of this information.

**WARRANTY**

Brady products are sold with the understanding that the buyers will test them in actual use and determine for themselves their adaptability to their intended uses. Brady warrants to the buyers that its products are free from defects in material and workmanship, but limits its obligation under this warranty to replacement of the product shown to Brady's satisfaction to have been defective at the time Brady sold it. This warranty does not extend to any persons obtaining the product from the buyers. This warranty is in lieu of any other warranty, express or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose, and of any other obligations or liability on Brady's part. Under no circumstances will Brady be liable for any loss, damage, expense, or consequential damages of any kind arising in connection with the use, or inability to use, Brady's products.

Copyright 2018 Brady Worldwide, Inc. | All Rights Reserved  
Material may not be reproduced or distributed in any form without written permission.

---

Brady North America | 6555 W. Good Hope Rd | Milwaukee, WI 53223 | USA | Tel: 414-358-6600 | Fax: 800-292-2289