




**Brady SPC UXT Xtra-Tough Absorbents**

TDS No. SPC-2  
Effective Date: 11/09/2015

**Description:**

The UXT line is designed for performance. With coverstock on both sides, these versatile, universal absorbents are low linting and abrasion resistant making them ideal for wiping applications.



**Details:**

**Color:**  
Dark Gray

**Composition:**  
100% Polypropylene

**Liquids Absorbed:**  
Oils, coolants, solvents, and water-based fluids

**Structure:**  
A nonwoven mat where the middle ply is made of randomly oriented Micro-fibers [2-10 micron diameters] and the coverstock layers are lint-resistant & abrasion resistant {controlled porosity} spunbond nonwoven of continuous filaments randomly oriented and thermally point bonded [15-30 micron diameters].

**Technology:**  
Meltblown & Spunbond, 3-ply

**Absorbency:**  
Universal (Hydrophilic + Oleophilic)

**Bonding:**  
Bonded (staggered pattern) + Mechanical entanglement

**Intended Application:**  
Low-Lint Chemical Resistant Sorbent for Water, Oil, or Solvent Base Liquids

**Physical Properties:**

Product	Absorbency	Absorbency Factor (gL/gS)	Absorbency Capacity (gal/L)	Basis Weight (G/M2)	Thickness (in/mm)	Tensile Strength (lbs/kg)
UXT100	Universal	11	19 / 71.9	290	0.180" / 4.57mm	28 / 12.7
UXT300	Universal	12	17 / 64.3	230	0.140" / 3.57mm	28 / 12.7
UXT200	Universal	14	31.5 / 119.2	190	0.100" / 2.5mm	28 / 12.7
UXT15-P	Universal	11	17 / 64.3	300	0.180" / 4.57mm	28 / 12.7
UXT30-DP	Universal	11	35 / 132.5	300	0.180" / 4.57mm	28 / 12.7

Product	Perforated?	Perforations Length (in/cm)	Perforation Width (in/cm)
UXT100	Yes		7.5" / 19.1cm
UXT300	Yes		7.5" / 19.1cm
UXT200	Yes		7.5" / 19.1cm
UXT15-P	Yes	18" / 45.7cm	15" / 38.1cm
UXT30-DP	Yes	15" / 38.1cm	15" / 38.1cm

**Packaging Properties:**

Product	Type	Size	Shipping Weight (lbs/kg)	Pallet Quantity	Quantity
UXT100	Heavy Weight Pad	15" x 19' / 38.1cm x 5.8m	14.5 / 6.6	30	100/case
UXT300	Medium Weight Pad	15" x 19' / 38.1cm x 5.8m	11 / 5.0	30	100/case
UXT200	Light Weight Pad	15" x 19' / 38.1cm x 5.8m	18.5 / 8.4	24	200/case
UXT15-P	Heavy Weight Roll	15" x 150' / 38.1cm x 45.7m	14.5 / 6.6	24	1/case
UXT30-DP	Medium Weight Roll	30" x 150' / 76.2cm x 45.7m	27.5 / 12.5	12	1/case

<b>Attributes</b>	Product will be free of foreign material contamination, rips, holes, and tears.
<b>Labeling</b>	Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code).
<b>Certification</b>	Claims for non-conformance of goods must be made within 60-days of delivery.

**Service Temperature:**

Up to 160°C (320°F)

**Trademarks:**

SPC® is a registered trademark of Brady Worldwide Inc.

**Note:** All values shown are averages and should not be used for specification purposes.

Test data and test results contained in this document are for general information only and shall not be relied upon by Brady customers for designs and specifications, or be relied on as meeting specified performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact Brady for further information.

Product compliance information is based upon information provided by suppliers of the raw materials used by Brady to manufacture this product or based on results of testing using recognized analytical methods performed by a third party, independent laboratory. As such, Brady makes no independent representations or warranties, express or implied, and assumes no liability in connection with the use of this information.

**WARRANTY**

Brady products are sold with the understanding that the buyers will test them in actual use and determine for themselves their adaptability to their intended uses. Brady warrants to the buyers that its products are free from defects in material and workmanship, but limits its obligation under this warranty to replacement of the product shown to Brady's satisfaction to have been defective at the time Brady sold it. This warranty does not extend to any persons obtaining the product from the buyers. This warranty is in lieu of any other warranty, express or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose, and of any other obligations or liability on Brady's part. Under no circumstances will Brady be liable for any loss, damage, expense, or consequential damages of any kind arising in connection with the use, or inability to use, Brady's products.

Copyright 2016 Brady Worldwide Inc. | All Rights Reserved  
Material may not be reproduced or distributed in any form without written permission.