



Brady SPC MRO® Plus Absorbents

TDS No. SPC-4
 Effective Date: 11/09/2015

Description:

Brady SPC's number one selling absorbent, MRO Plus® products are sure to become a staple in your facility. Strong, durable and low linting, these are the perfect everyday go-to products for nearly every industrial setting.



Details:

Color:
 Gray

Composition:
 100% Polypropylene

Liquids Absorbed:
 Oils, coolants, and water-based fluids

Structure:
 A nonwoven mat of randomly oriented Micro-fibers [2-10 micron diameters]

Technology:
 Meltblown, 3-ply

Absorbency:
 Universal (**Hydrophilic** + Oleophilic)

Bonding:
 Bonded (staggered pattern) + Mechanical entanglement

Intended Applications:
 Low-Lint Chemical Resistant Sorbent for Water, Oil, or Solvent Base Liquids

Physical Properties:

Product	Absorbency	Absorbency Factor (g/L/gS)	Absorbency Capacity (gal/L)	Basis Weight (G/M2)	Thickness (in/mm)	Tensile Strength (lbs/kg)
MRO50	Universal	12.5	41 / 155.2	370	0.195" / 4.95mm	18 / 8.2
MRO150DND	Universal	12.5	39 / 147.6	370	0.195" / 4.95mm	18 / 8.2
MRO100	Universal	12.5	26 / 98.4	370	0.195" / 4.95mm	18 / 8.2
MRO100-2	Universal	12.5	13.5 / 51.1	370	0.195" / 4.95mm	18 / 8.2
MRO300	Universal	12.5	20.5 / 77.6	290	0.175" / 4.45mm	16 / 7.3
MRO30DP	Universal	12.5	49 / 185.5	370	0.195" / 4.95mm	18 / 8.2
MRO30P	Universal	12.5	49 / 185.5	370	0.195" / 4.95mm	18 / 8.2
MRO30	Universal	12.5	49 / 185.5	370	0.195" / 4.95mm	18 / 8.2

MRO24DP	Universal	12.5	39 / 147.6	370	0.195" / 4.95mm	18 / 8.2
MRO15DP	Universal	12.5	24 / 90.8	370	0.195" / 4.95mm	18 / 8.2
MRO15P	Universal	12.5	24 / 90.8	370	0.195" / 4.95mm	18 / 8.2
MRO15	Universal	12.5	24 / 90.8	370	0.195" / 4.95mm	18 / 8.2
MRO15DPS	Universal	12.5	12 / 45.4	370	0.195" / 4.95mm	18 / 8.2
MRO12P	Universal	12.5	20 / 75.7	370	0.195" / 4.95mm	18 / 8.2
MRO350DP	Universal	12.5	38 / 143.8	290	0.175" / 4.45mm	18 / 8.2
MRO350	Universal	12.5	38 / 143.8	290	0.175" / 4.45mm	16 / 7.3
MRO315P	Universal	12.5	20 / 75.7	290	0.175" / 4.45mm	16 / 7.3

Product	Perforated?	Perforation Length (in/cm)	Perforation Width (in/cm)
MRO50	Yes		15" / 38.1cm
MRO150DND	Yes		7.5" / 19.1cm
MRO100	Yes		7.5" / 19.1cm
MRO100-2	Yes		7.5" / 19.1cm
MRO300	Yes		7.5" / 19.1cm
MRO30DP	Yes	15" / 38.1cm	15" / 38.1cm
MRO30P	Yes	30" / 76.2cm	
MRO30	No		
MRO24DP	Yes	12" / 30.5cm	12" / 30.5cm
MRO15DP	Yes	12" / 30.5cm	7.5" / 19.1cm
MRO15P	Yes	18" / 45.7cm	
MRO15	No		
MRO15DPS	Yes	12" / 30.5cm	7.5" / 19.1cm
MRO12P	Yes	12" / 30.5cm	
MRO350DP	Yes	15" / 38.1cm	15" / 38.1cm
MRO350	No		
MRO315P	Yes	18" / 45.7cm	

Packaging Properties:

Product	Type	Size	Shipping Weight (lbs/kg)	Pallet Quantity	Quantity
MRO50	Heavy Weight Pad	30" x 30" / 76.2cm x 76.2cm	26.5 / 12.0	13	50/bale
MRO150DND	Heavy Weight Pad	15" x 19" / 38.1cm x 48.3cm	27 / 12.3	18	150/case
MRO100	Heavy Weight Pad	15" x 19" / 38.1cm x 48.3cm	17.5 / 7.9	30	100/case
MRO100-2	Heavy Weight Pad	15" x 19" / 38.1cm x 48.3cm	8 / 3.6	36	50/bale
MRO300	Medium Weight Pad	15" x 19" / 38.1cm x 48.3cm	14 / 6.4	30	100/case
MRO30DP	Heavy Weight Roll	30" x 150' / 76.2cm x 45.7m	32 / 14.5	12	1/case
MRO30P	Heavy Weight Roll	30" x 150' / 76.2cm x 45.7m	32 / 14.5	12	1/case
MRO30	Heavy Weight Roll	30" x 150' / 76.2cm x 45.7m	33 / 15.0	12	1/case
MRO24DP	Heavy Weight Roll	24" x 150' / 61.0cm x 45.7m	22.5 / 10.2	27	1/bale
MRO15DP	Heavy Weight Roll	15" x 150' / 38.1cm x 45.7m	17.5 / 7.9	30	1/case
MRO15P	Heavy Weight Roll	15" x 150' / 38.1cm x 45.7m	17.5 / 7.9	30	1/case
MRO15	Heavy Weight Roll	15" x 150' / 38.1cm x 45.7m	17.5 / 7.9	30	1/case
MRO15DPS	Heavy Weight Roll	15" x 73' / 38.1cm x 22.3m	8 / 3.6	80	1/bale
MRO12P	Heavy Weight Roll	12" x 150' / 30.5cm x 45.7m	11.5 / 5.2	36	1/bale
MRO350DP	Medium Weight Roll	30" x 150' / 76.2cm x 45.7m	26.5 / 12.0	12	1/case
MRO350	Medium Weight Roll	30" x 150' / 76.2cm x 45.7m	26.5 / 12.0	12	1/case
MRO315P	Medium Weight Roll	15" x 150' / 38.1cm x 45.7m	14 / 6.4	30	1/case

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery.

Service Temperature:

Up to 160°C (320°F)

Trademarks:

SPC MRO Plus® is a registered trademark of Brady Worldwide Inc.

Note: All values shown are averages and should not be used for specification purposes.

Test data and test results contained in this document are for general information only and shall not be relied upon by Brady customers for designs and specifications, or be relied on as meeting specified performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact Brady for further information.

Product compliance information is based upon information provided by suppliers of the raw materials used by Brady to manufacture this product or based on results of testing using recognized analytical methods performed by a third party, independent laboratory. As such, Brady makes no independent representations or warranties, express or implied, and assumes no liability in connection with the use of this information.

WARRANTY

Brady products are sold with the understanding that the buyers will test them in actual use and determine for themselves their adaptability to their intended uses. Brady warrants to the buyers that its products are free from defects in material and workmanship, but limits its obligation under this warranty to replacement of the product shown to Brady's satisfaction to have been defective at the time Brady sold it. This warranty does not extend to any persons obtaining the product from the buyers. This warranty is in lieu of any other warranty, express or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose, and of any other obligations or liability on Brady's part. Under no circumstances will Brady be liable for any loss, damage, expense, or consequential damages of any kind arising in connection with the use, or inability to use, Brady's products.

Copyright 2016 Brady Worldwide Inc. | All Rights Reserved
Material may not be reproduced or distributed in any form without written permission.

SPC Sorbents | 7201 National Turnpike | Louisville, KY 40214 | USA | Tel: 1-414-358-6600 | Fax: 800-292-2289